

Be Your Window To The World



Picture and logos

SELLING POINTS

- Perfect 27" screen size for the programming, coding & website design workspace.
- TÜV certified display ensures the protection and health of eyesight.
- MSI EyesErgo technology with Anti-Flicker and Less Blue Light technology helps prevent eye strain and fatigue.
- 100 Hz refresh rate provides a better viewing experience with flicker-free image.
- MSI Eye-Q Check helps have self-check eyes & reminds to take a rest while using the monitor for a long time.
- The stand is designed with ergonomic features, including tilt, swivel, height, and pivot adjustments.
- Maintain versatility across various devices by utilizing multiple input sources, such as HDMI™ and D-Sub(VGA) ports.
- Standard VESA mountable design.
- Two built-in speakers.



1. 1x DC-in
2. 1x HDMI (1.4b)
3. 1x D-Sub (VGA)
4. 1x Line-in
5. 1x Headphone-out
6. 1x Kensington Lock
7. 1x 5-way navigator



SPECIFICATION

Barcode Info	EAN	4711377128742
	UPC	824142334713
	UCC14	10824142334710
Model	Part No	9S6-3PC39M-015
	MKT Name	PRO MP275P
	MKT Spec	PRO MP275P
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	598(H) x 336(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.416~112.5 KHz(H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	81%/78%
	NTSC (CIE1931 area percentage/overlap)	72%/70%
	sRGB (CIE1976 area percentage/overlap)	93%/88%
	sRGB (CIE1931 area percentage/overlap)	99%/92%
	Adobe RGB (CIE1976 area percentage/overlap)	79%/77%
	Adobe RGB (CIE1931 area percentage/overlap)	74%/71%
	DCI-P3 (CIE1976 area percentage/overlap)	74%/73%
	DCI-P3 (CIE1931 area percentage/overlap)	74%/74%
	Rec.709 (CIE1976 area percentage/overlap)	93%/88%
	Rec.709 (CIE1931 area percentage/overlap)	99%/92%
	Rec.2020 (CIE1976 area percentage/overlap)	53%/53%
	Rec.2020 (CIE1931 area percentage/overlap)	52%/52%
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
	Note_HDMI™	1920 X 1080 (Up to 100Hz)
	Note_DVI	N/A
I/O Ports	Line-in	1
	HDMI™	1
	HDMI™ version	1.4b
	HDMI™ HDCP version	1.4
	D-Sub	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2
I/O Ports (Rear)	Card Reader	N/A
Power	Annual Energy Consumption (KWh)	N/A
	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	E
	Adapter's KC safety Number	N/A
	Power Cord Type	C13
	QC Output Power	N/A
	PD Output Power	N/A



In The Box	3.5mm Mic Cable	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	0
	Warranty Card	0
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 120 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (inch)	N/A
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	612.1 x 228.9 x 542.4
	Product Dimension with Stand (WxDxH) (inch)	24.1 x 9.01 x 21.35
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	612.1 x 56.3 x 363.0
	Product Dimension without Stand (WxDxH) (inch)	24.1 x 2.22 x 14.29
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	224.2 x 228.9 x 383.9
	Stand Dimension (WxDxH) (inch)	8.83 x 9.01 x 15.11
Dimension & Weight	Inside Carton Dimension (WxDxH) (inch)	N/A
	Weight (Net kg)	5.28
	Weight (Gross kg)	7.
Weight	Weight Without Stand (kg)	3.41
Warranty	Warranty	36M